

The Headphone Test Module (AIO-H) is designed for making advanced acoustic and impedance measurements of a device under test (DUT)—typically wired headphones, headsets, earbuds, and hearing protection devices. AIO-H is a configuration option for the AIO Test System and requires the AIO chassis to operate.



HARDWARE FEATURES:

- Two mic/line inputs
- CCP/IEPE/ICP microphone power
- TEDS reader for microphone data
- Two single-ended headphone outputs
- Internal impedance sense resistor
- Additional inputs for voltage and current monitoring

KEY APPLICATIONS:

- Headphones & earbuds
- Mobile devices

MIC/LINE INPUTS:


Two low-noise inputs accommodate a very wide range of input voltages, from dynamic microphones to line-level inputs. Features include adjustable gain, constant current power, and TEDS readers.

HEADPHONE OUTPUTS:

Two high-quality single-ended outputs optimized for driving headphones and earbuds.

PERFORMANCE GRAPHS:


Mic/Line Inputs



IMPEDANCE MEASUREMENT:

Two additional inputs are used to measure load impedance via the remote voltage sense terminals and internal sense resistors. These inputs appear as additional audio input channels and can be switched to measure either output channel via the AIO control panel, or the command-line or API interfaces.

Headphone Outputs



The Echo AIO™ is a modular audio test platform ideally suited for high-volume production-line testing and QA/QC verification. The AIO combines the functionality of multiple standalone devices into a single, integrated unit, making test stations both more reliable and less expensive.

HEADPHONE MODULE COMMON CONFIGURATIONS: (Other configurations may be available—check with your dealer.)

Model	Inner Module	Outer Module	Mic/Line Inputs	Line Outputs	Headphone Outputs	Amp Outputs	Impedance	Digital	5VDC & Battery Simulator	GPIO	PTH
AIO-AH	AIO-A	AIO-H	6		2		1				
AIO-H1	AIO-H		2		2		1				
AIO-H2	AIO-H	AIO-H	4		4		2				

SPECIFICATIONS:

Microphone / Line Inputs	
Input bandwidth	72 kHz
Input impedance	1 M Ω
Input gain	1x, 10x, and 100x
Full-scale input voltage (1x gain)	8.75 Vpk
Maximum input voltage	15 Vpk (do not exceed)
Dynamic range (1x gain, A-wtd)	> 110 dB
THD+N (1x gain, A-weighted)	< -95 dB (20 Hz – 20 kHz)
Frequency response	± 0.5 dB (20 Hz – 20 kHz)
Constant current supply	CCP/IEPE/ICP, 4 mA
TEDS	IEEE 1451.4 Class 1

Headphone Outputs	
Output power (THD+N < .1%)	375mW (125 mA max)
Maximum output voltage	3 Vrms
Frequency response	± 0.1 dB (20 Hz – 20 kHz)
Minimum load	16 Ω

Impedance Measurement:	
Full-scale input voltage	3 Vrms
Full-scale input current	125 mA
THD+N (A-weighted)	< -95 dB (20 Hz – 20 kHz)
Frequency response	± 0.5 dB (20 Hz – 20 kHz)

Interface	
Sample rates	44.1 kHz – 192 kHz
USB	USB 2.0 audio class compliant
Supported operating systems	Windows 10 or later, macOS
Audio APIs	ASIO, WASAPI, Core Audio
AC power	90 – 264 VAC, 50/60 Hz, 60 W

Dimensions and Weight	
Single unit	17.5" (44.4 cm) x 8.75" (22.2 cm) x 1.75" (4.4 cm), 7.2 lbs (3.3 kg)
Single unit boxed with cables	21" (53 cm) x 10" (25.4 cm) x 5" (12.7 cm), 8.75 lbs (4 kg)
Carton (4 units)	22" (55.8 cm) x 22" (55.8 cm) x 12.6" (32 cm), 42.5 lbs (19.3 kg)

AIO Test System

(see system datasheet for more details)



Shown: AIO-H2 rear view with two AIO-H headphone test modules.

FEATURES:

- High accuracy
- Cost effective
- Silent—no fan!
- Standard USB audio interface
- Wide test & measurement software compatibility
- ASIO, WASAPI, & Core Audio protocols



CONTROL PANEL SOFTWARE:

Provides comprehensive level monitoring and control over hardware settings, including transducer power, TEDS data, gain, TDM format, and calibration. Command-line and API access to settings is also available.

TEST & MEASUREMENT SOFTWARE:

Choose from a wide variety of third-party test and measurement software, including APx500 Flex, ARTA, LabVIEW, and MATLAB. The AIO system works just like a standard sound card for Windows, Mac, or Linux.


Echo Test + Measurement

402 E Carrillo St Ste A, Santa Barbara CA 93101 USA
 echotm.com sales@echotm.com +1 805-880-5590

MODULE OPTIONS:

(see individual datasheets for details and configurations)

- A Acoustic:** Four mic/line inputs with CCP, TEDS; two 10 W class-D amplifier outputs.
- C Combo:** GPIO; 5 VDC fixed supply; 5 VDC battery simulator; Pressure, temperature, and humidity sensor.
- H Headphone:** Four mic/line inputs with CCP, TEDS; two headphone/earbud outputs with impedance measurement.
- L Line Level:** Four mic/line inputs with CCP, TEDS; two balanced line-level outputs.
- S Speaker:** Two mic/line inputs with CCP, TEDS; two 10 W class-D amplifier outputs; built-in speaker impedance measurement.
- T TDM:** Digital TDM, up to 10 channels, 24 or 32 bit samples, 192 kHz.



Specifications are subject to change without notice. All trademarks or registered trademarks are the property of their respective owners. The AIO Test System is CE compliant.

Copyright © 2022 Echo Test + Measurement

XXII07141825 rev 2