

TESTEC ACTIVE DIFFERENTIAL PROBES

TT-SX 9001 / TT-SX 9002



	TT-SX 9001	TT-SX 9002
Order Number	15601	15602
Attenuation Ratio	x10 / x100	x 20 / x200
DC-Accuracy	±2%	±2%
Bandwidth (-3dB)	30 MHz	30 MHz
Max. Differential Input Voltage (DC + peak AC)	±70 V @ x10 ±700 V @ x100	±140 V @ x200 ±1400 V @ x200
Max. Common Mode Input Voltage (DC + peak AC)	±70 V @ x10 ±700 V @ x100	±140 V @ x20 ±1400 V @ x200
Absolute Maximum Input Voltage (each side to ground)	1000V CAT III	
Safety Standard	IEC1010-031:2015 – CAT III	
Power requirements	4 x AA batteries or USB-C cable	

ADMESS

ADMESS Vertriebs GmbH
Ernst-Kiefer-Straße 9
67292 Kirchheimbolanden /Germany

Tel.: +49 (0) 6352 / 78 99 8 - 0 Telefax: +49 (0)
6352 / 78 99 8 - 20 E-Mail: info@admess.de
www.admess.de

TESTEC

Technical data subject to change
© Testec Elektronik GmbH 2022
info@testec.de
www.testec.de