## **TESTEC ACTIVE DIFFERENTIAL PROBES 7000 SERIES**

The new TT-SI 7000 series active differential probes allow safe, accurate measurements between two voltage points where neither point is referenced to ground. These probes are perfect designed for a wide variety of measurements and are compatible with oscilloscopes from all major manufacturers.



	TT-SI 7002	TT-SI 7005
Order Number	15175	15176
Attenuation	x20, x50, x200	1x, x5, x10
DC-Accuracy	±2%	
Bandwidth	25MHz @ x50 and x200	60MHz @ x10
	15MHz @ x20	50MHz @ x5
		15MHz @ x1
Max. Input Voltage	±70V (DC + AC peak) @ x20	±3,5V (DC + AC peak) @ x1
	±175V (DC + AC peak) @ x50	±18V (DC + AC peak) @ x5
	±700V (DC + AC peak) @ x200	±35V (DC + AC peak) @ x10
Absolute Maximum Input Voltage	600Vrms (each side to ground)	
Safety Standard	IEC1010-031:2015 – CAT III	
Supplied Accessories	2 x Test Leads with insulated 4mm Banana Plugs (red & black)	
	2 x Grabbers (red & black), 1 x Insulated BNC Cable - 100cm	
	1 x Mains Adapter 220V EU Version	



ADMESS Vertriebs GmbH Ernst-Kiefer-Straße 9 67292 Kirchheimbolanden /Germany

Technical data subject to change © Testec Elektronik GmbH 2019

TESTEC

Tel.: +49 (0) 6352 / 78 99 8 - 0 Telefax: +49 (0) 6352 / 78 99 8 - 20 E-Mail: info@admess.de

www.admess.de