



Model / Order-No.	TT-HVP 15B / 15010
Division Ratio	1000:1
Input Resistance	100M Ω
Input Capacitor	3,0pF \pm 0,5pF
Max. DC+AC peak	20kV CAT 0
Max. AC RMS.	7kV CAT 0
Max. DC	10kV CAT 0
Band Width	DC~40MHz (-3dB)
Rise Time	\leq 8,8ns
Signal / Noise	DC: > 60dB @ 1kHz ; > 50dB @ 1MHz
DCV Accuracy	\leq 6%
Temp. Coefficient	\leq 200 ppm/ $^{\circ}$ C
Compensation Range	15pF ~ 30pF
Safety Standard	meets IEC61010-031:2015
Measurement Category	CAT 0 / Pollution Degree 2
Cable Length	2m \pm 0.2m
Operation Temp.	-10 $^{\circ}$ C to 55 $^{\circ}$ C
Humidity	85% RH or less (@ 35 $^{\circ}$ C)
Storage Temp.	-20 $^{\circ}$ C to 70 $^{\circ}$ C
Color: Handel / Body	Black / Yellow
Weight / Volume	250g / 75(W) x 75(H) x 340(L) mm

Fritz-Klatte-Str. 6,D - 65933 Frankfurt / E-Mail: info@testec.de
 Telefon: +49 (0) 69 - 94 333 5 – 0, Fax: +49 (0) 69 - 94 333 5 - 55

Specifications are subject to change without notice